Icemos
Cooler than cool

Preliminary Data Sheet

ICE20N170FP

ICE20N170FP N-Channel Enhancement Mode MOSFET

RoHS compliant 2011/65/EU


CE

HALOGEN FREE

Product Summary			
I_D	T_A=25°C	20A	Max
$V_{(BR)DSS}$	I_D=250uA	600V	Min
$r_{DS(on)}$	V_{GS}=10V	0.17Ω	Typ
Q_g	V_{DS}=480V	62nC	Typ

Features

- Low $r_{DS(on)}$
- Ultra Low Gate Charge
- High d*v*/d*t* capability
- High Unclamped Inductive Switching (UIS) capability
- High peak current capability
- Increased transconductance performance
- Optimized design for high performance power systems





T0220 Full-PAK

Isolated (T0-220)

1=Gate, 2=Drain, 3=Source

ICEMOS AND ITS SISTER COMPANY 3D SEMI OWN THE FUNDAMENTAL PATENTS FOR SUPERJUNCTION MOSFETS. THE MAJORITY OF THESE PATENTS HAVE 17 to 20 YEARS OF REMAINING LIFE. THIS PORTFOLIO HAS GRANTED PATENTS ISSUED IN USA, CHINA, KOREA, JAPAN, TAIWAN & EUROPE.

Maximum ratings [b] , at T_j=25°C, unless otherwise specified

Parameter	*Symbol*	*Conditions*	*Value*	*Unit*
Continuous drain current	I_D	T_c=25°C	20	A
Pulsed drain current	$I_{D, pulse}$	T_c=25°C	62	A
Avalanche energy, single pulse	E_{AS}	I_D=10A	520	mJ
Avalanche current, repetitive	I_{AR}	limited by $T_j$max	20	A
MOSFET d*v*/d*t* ruggedness	d*v*/d*t*	V_{DS}=480V, I_D=20A, T_j=125°C	50	V/ns
Gate source voltage	V_{GS}	Static	±20	V
		AC (*f*>1Hz)	±30	
Power dissipation	P_{tot}	T_c=25°C	35	W
Operating and storage temperature	T_j, T_{stg}		-55 to +150	°C
Mounting torque		M 2.5 screws	50	Ncm


a When mounted on 1inch square 2oz copper clad FR-4

b Preliminary Data Sheet – Specifications subject to change


Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	
Thermal characteristics						
Thermal resistance, junction-case [a]	R_{thJC}		-	-	3.5	°C/W
Thermal resistance, junction-ambient [a]	R_{thJA}	leaded	-	-	72	
Soldering temperature, wave soldering only allowed at leads	T_{sold}	1.6mm (0.063in.) from case for 10 s	-	-	260	°C
Electrical characteristics [b], at T_j=25°C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=250µA	600	640	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250µA	2.1	3	3.9	
Zero gate voltage drain current	I_{DSS}	V_{DS}=600V, V_{GS}=0V, T_j=25°C	-	0.1	1	µA
		V_{DS}=600V, V_{GS}=0V, T_j=150°C	-	-	100	
Gate source leakage current	I_{GSS}	V_{GS}=±20 V, V_{DS}=0V	-	-	100	nA
Drain-source on-state resistance	$R_{DS\ (on)}$	V_{GS}=10V, I_D=10A, T_j=25°C	-	0.17	0.199	Ω
		V_{GS}=10V, I_D=10A, T_j=150°C	-	0.52	-	
Gate resistance	R_G	f=1 MHZ, open drain	-	4.3	-	Ω
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=25 V, f=1 MHz	-	2020	-	pF
Output capacitance	C_{oss}		-	980	-	
Reverse transfer capacitance	C_{rss}		-	9	-	
Transconductance	g_{fs}	V_{DS}>2*I_D*R_{DS}, I_D=10A	-	19	-	S
Turn-on delay time	$t_{d(on)}$	V_{DS}=380V, V_{GS}=10V, I_D=20A, R_G=4Ω (External)	-	39	-	ns
Rise time	t_r		-	3.5	-	
Turn-off delay time	$t_{d(off)}$		-	55	-	
Fall time	t_f		-	7	-	

Parameter	Symbol	Conditions	Values			Unit
			Min	Typ	Max	
Gate charge characteristics						
Gate to source charge	Q_{gs}	V_{DS}=480 V, I_D=20A, V_{GS}=10 V	-	13	-	nC
Gate to drain charge	Q_{gd}		-	23	-	
Gate charge total	Q_g		-	62	-	
Gate plateau voltage	$V_{plateau}$		-	5.8	-	V
Reverse Diode						
Diode forward voltage	V_{SD}	V_{GS}=0V, I_S=I_F	-	0.9	1.2	V
Reverse recovery time	t_{rr}	V_{RR}=480V, I_S=I_F, d_{iF}/d_t=100 A/µS	-	407	-	ns
Reverse recovery charge	Q_{rr}		-	6.7	-	µC
Peak reverse recovery current	I_{rm}		-	32	-	A


Output Characteristics




Transfer Characteristics




On Resistance vs Drain Current




On Resistance vs Junction Temperature




Gate Charge




Gate Threshold Voltage vs Junction Temperature




Capacitance




Drain-to-Source Breakdown Voltage vs. Junction Temperature




Maximum Rated Forward Biased Safe Operating Area



Transient Thermal Response, Junction-to-Case




D
Q
H1
F1
b2
G3
b1
e
G
G1
E
(E1)
E2
K1
(L1)
L2
F4
L
ØP
2-ØP2
6-ØP1
θ1
θ2
A5
DEP
A
A1
c
A4
A2
θ1
DEP
G1
ØP3
F1
F3
F2

COMMON DIMENSIONS						
SYMBOL	MM			INCH		
	MIN	NOM	MAX	MIN	NOM	MAX
E	9.63	10.19	10.75	0.38	0.40	0.42
E1	9.94	10.04	10.14	0.39	0.40	0.40
E2	9.36	9.46	9.56	0.37	0.37	0.38
A	4.30	4.60	4.90	0.17	0.18	0.19
A1	2.34	2.77	3.20	0.092	0.11	0.126
A2	0.43	0.87	1.30	0.017	0.03	0.051
A4	2.51	2.72	2.93	0.10	0.11	0.12
A5		1.00REF			0.39REF	
c	0.33	0.54	0.75	0.013	0.021	0.030
D	15.67	15.9	16.13	0.617	0.626	0.635
Q		9.4REF			0.370REF	
H1		6.7REF			0.264REF	
E		2.54BSC			0.100BSC	
ΦP		3.18REF			0.125REF	
L	12.78	13.25	13.72	0.50	0.52	0.54
L1	2.83	3.25	3.67	0.11	0.13	0.14
L2	7.70	7.80	7.90	0.30	0.31	0.31
ΦP1	1.4	1.5	1.6	0.055	0.059	0.063
ΦP2	1.15	1.2	1.25	0.045	0.047	0.049
ΦP3		3.45REF			0.136REF	
θ1	3°	5°	7°	3°	5°	7°
θ2	-	45°	-	-	45°	-
DEP	0.05	0.10	0.15	0.002	0.004	0.006
F1	1.0	1.50	2.0	0.039	0.059	0.079
F2	13.8	13.90	14.0	0.543	0.547	0.551
F3	3.20	3.30	3.40	0.126	0.130	0.134
F4	5.30	5.40	5.50	0.209	0.213	0.217
G	7.80	8.00	8.20	0.307	0.315	0.323
G1	6.05	6.58	7.10	0.238	0.259	0.280
G3	1.25	1.35	1.45	0.049	0.053	0.057
b1	1.23	1.31	1.38	0.048	0.051	0.054
b2	0.61	0.78	0.94	0.024	0.031	0.037
K1	0.65	0.70	0.75	0.026	0.028	0.030
R		0.50REF			0.020REF	

ICEMOS SUPERJUNCTION PATENT PORTFOLIO

ICEMOS GRANTED PATENTS

US7,429,772
US7,439,178
US7,446,018
US7,579,607
US7,723,172
US7,795,045
US7,846,821
US7,944,018
US8,012,806
US8,030,133

3D SEMI PATENTS LICENSED TO ICEMOS

US7,041,560B2
US7,023,069B2
US7,364,994
US7,227,197B2
US7,304,944B2
US7,052,982B2
US7,339,252
US7,410,891
US7,439,583
US7,227,197B2
US6,635,906
US6,936,867
US7,015,104
US9,109,110
US7,271,067
US7,354,818
US7,052,982,
US7,199,006B2

Note: additional patents in China, Korea, Japan, Taiwan, Europe have also been granted to IceMOS and 3D Semi for Superjunction MOSFETs with 70 additional Patent applications in process in the USA and the above listed countries.

Marking Information

YY = Last two digits of the year

WW = Work week calendar on Icemos subcon assembly & test house

***** = Initial for Icemos subcon assembly and test house

XXXX = Wafer Lot ID

00 = may be used for wafer ID in a special case.
= "00" is used unless specified.

ICE20N170 = ICE is Icemos logo and 20N170 is a designated device part number

